TECHNICAL DATA SHEET

Language	ENGLISH	
Subject	EUROSINT 2 EVO	
	100% synthetic ester based 2-stroke oil	



our **power**, your **passion**

EUROSINT 2 EVO

OLEO-MAC EUROSINT 2 EVO

100% synthetic ester based 2-stroke oil, for highly stressed engines in gardening equipment.

Description		Benefits		
xclusively developed for highly stressed 2-stroke ngines, based on synthetic esters with outstanding ubricating and anti-wear properties.		100% synthetic ester.Exceptional performance and superior engine protection.		
The product can be easily mixed with all kind of fuels, no matter the outside temperature.		Very high load resistance.		
Its specific additive package allows the fuel-oil mixture to remain stable even if not used, for long periods				
Specifications				
API TC				
JASO FD				
• ISO-L-EGD				

Average Typical Data

Properties	Unit	Value	Test Method
SAE Grade		40	
Colour		Blue	
Density @ 20°C	Kg/l	0.920	ASTM D 1298
Viscosity @ 40°C	mm²/s	98.60	ASTM D 445
Viscosity @ 100°C	mm²/s	13.50	ASTM D 445
Viscosity Index		137	ASTM D 2270

Application

Suitable for all high performance 2-stroke, air-cooled and water-cooled engines of gardening equipment, chainsaws, lawnmowers, etc.

It can be used both with normal and unleaded petrol.

Mixture from 2 to 3% are accepted, as specified by the manufacturer.

Also suitable for competition 2-stroke engines (motorcycles, karts ...).



It's an Emak S.p.A. trademark 42011 Bagnolo in Piano (RE) Italy www.oleomac.com www.youtube.com/MyOleoMac www.facebook.com/OleoMacItalia www.instagram.com/OleoMacItalia